

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : Pyroil™ STARTING FLUID

Product code : PYSFR11

Manufacturer or supplier's details

Company name of supplier : Niteo Products,LLC

Address : Dallas TX 19162

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable aerosols : Category 1

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity
- single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

H361d Suspected of damaging the unborn child.

Precautionary statements**: Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Substance name	: Valvoline International

Hazardous components

Pyroil™ STARTING FLUID

Version 1.1 Revision Date: 04/21/2017 SDS Number: 600000000538 Date of last issue: 05/23/2016
Date of first issue: 05/23/2016

Chemical name	CAS-No.	Concentration (% w/w)
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	>= 70 - < 90
ETHYL ETHER	60-29-7	>= 10 - < 20
n-HEPTANE	142-82-5	>= 1 - < 5
CARBON DIOXIDE	124-38-9	>= 1 - < 5
ETHANOL	64-17-5	>= 1 - < 5
ETHYL CHLORIDE	75-00-3	>= 0.1 - < 1
TOLUENE	108-88-3	>= 0.1 - < 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
Keep patient warm and at rest.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging the unborn child.

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Suitable extinguishing media | : Water spray
Carbon dioxide (CO2)
Dry chemical
Alcohol-resistant foam |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities. |
-

SECTION 7. HANDLING AND STORAGE

- | | |
|---|--|
| Advice on protection against fire and explosion | : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away |
|---|--|
-

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked flame or any incandescent material.

- Advice on safe handling : Open drum carefully as content may be under pressure. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Dispose of rinse water in accordance with local and national regulations. Container hazardous when empty. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYL ETHER	60-29-7	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	400 ppm 1,200 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,200 mg/m ³	OSHA P0
n-HEPTANE	142-82-5	STEL	500 ppm 1,500 mg/m ³	OSHA P0
		TWA	85 ppm 350 mg/m ³	NIOSH REL
		C	440 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		STEL	500 ppm 2,000 mg/m ³	OSHA P0

Pyroil™ STARTING FLUID

Version 1.1 Revision Date: 04/21/2017 SDS Number: 600000000538 Date of last issue: 05/23/2016
 Date of first issue: 05/23/2016

CARBON DIOXIDE	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
ETHANOL	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
ETHYL CHLORIDE	75-00-3	TWA	100 ppm	ACGIH
		TWA	1,000 ppm 2,600 mg/m3	OSHA Z-1
		TWA	1,000 ppm 2,600 mg/m3	OSHA P0
TOLUENE	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
TOLUENE	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As)	0.03 mg/l	ACGIH BEI

Pyroil™ STARTING FLUID

Version 1.1 Revision Date: 04/21/2017 SDS Number: 600000000538 Date of last issue: 05/23/2016
 Date of first issue: 05/23/2016

				soon as possible after exposure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
 In the case of dust or aerosol formation use respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear as appropriate:
 Impervious clothing
 Flame-resistant clothing
 Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 When using do not smoke.
 When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol
Odour : No data available
pH : No data available

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

	: No data available
Boiling point/boiling range	: 34.6 °C (1,013.232 hPa) The value is calculated
Flash point	: -45 °C The value is calculated
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 36.5 %(V) The value is calculated
Lower explosion limit	: 1.05 %(V) The value is calculated
Vapour pressure	: 717.2616 hPa (25 °C) The value is calculated
Density	: 0.7114 g/cm3 (15.56 °C)
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Heat Heat, flames and sparks.
Incompatible materials	: Acids Alkali metals Ammonia

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

Bases
halogens
Oxidizing agents
Sulphur compounds

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 2,557 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 14.19 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:**SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

Acute oral toxicity : LD50 (Rat): > 8,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3400 ppm
Exposure time: 4 h
Test atmosphere: vapour

ETHYL ETHER:

Acute oral toxicity : LD50 (Rat): 1,200 - 1,700 mg/kg

n-HEPTANE:

Acute oral toxicity : LD50 (Rat): Expected > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC50 (Rat, male and female): > 29.29 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): Expected > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.
Remarks: Information given is based on data obtained from similar substances.

ETHANOL:

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

Acute oral toxicity : LD50 (Rat): 7,060 mg/kg

Acute inhalation toxicity : LC50 (Rat): 117 - 125 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LDLo (Rabbit): 20 g/kg

ETHYL CHLORIDE:

Acute inhalation toxicity : LC50 (Rat): > 19000 ppm
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

TOLUENE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 8000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation and/or dermatitis.

Components:**SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

Result: Possibly irritating to skin

ETHYL ETHER:

Result: Irritating to skin.

n-HEPTANE:

Result: Irritating to skin.

CARBON DIOXIDE:

Assessment: No skin irritation

Result: No skin irritation

ETHANOL:

Result: Possibly irritating to skin

ETHYL CHLORIDE:

Result: Possibly irritating to skin

TOLUENE:

Result: Irritating to skin.

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

Result: Possibly irritating to eyes

ETHYL ETHER:

Result: Irritating to eyes.

n-HEPTANE:

Result: Possibly irritating to eyes

CARBON DIOXIDE:

Result: No eye irritation

ETHANOL:

Result: Irritating to eyes.

ETHYL CHLORIDE:

Result: Possibly irritating to eyes

TOLUENE:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**n-HEPTANE:**

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

Germ cell mutagenicity

Not classified based on available information.

Components:**n-HEPTANE:**

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Carcinogenicity

Suspected of causing cancer.

Components:**ETHYL CHLORIDE:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:**TOLUENE:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**ETHYL ETHER:**

Assessment: May cause drowsiness or dizziness.

n-HEPTANE:

Assessment: May cause drowsiness or dizziness.

ETHANOL:

Assessment: May cause drowsiness or dizziness.

TOLUENE:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:**TOLUENE:**

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

May be fatal if swallowed and enters airways.

Components:**SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:**

May be fatal if swallowed and enters airways.

n-HEPTANE:

May be fatal if swallowed and enters airways.

TOLUENE:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
-----------	-----------

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 1950

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

ERG Code : 126

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Component RQ (lbs)
ETHYL ETHER	60-29-7	100	100
TOLUENE	108-88-3	1000	1000
BENZENE	71-43-2	10	10
ETHYL CHLORIDE	75-00-3	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard
Fire Hazard
Acute Health Hazard
Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

US State Regulations
Massachusetts Right To Know

ETHYL ETHER	60-29-7
n-HEPTANE	142-82-5
CARBON DIOXIDE	124-38-9
ETHANOL	64-17-5
BENZENE	71-43-2

Pennsylvania Right To Know

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8
ETHYL ETHER	60-29-7
n-HEPTANE	142-82-5
CARBON DIOXIDE	124-38-9
ETHANOL	64-17-5
ETHYL CHLORIDE	75-00-3
TOLUENE	108-88-3


California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.
WARNING! This product contains a chemical known to the State of California to cause cancer.
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION
Further information
NFPA:

HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Pyroil™ STARTING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	04/21/2017	600000000538	Date of first issue: 05/23/2016

Revision Date : 04/21/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN